

UniQa

Design by Favaretto & Partners

UniQa is a chair ideal for executive and elegant office settings. The solid die-cast aluminum structure forms a harmonious graphic shape that supports the height-adjustable backrest, upholstered in either leather or fabric. The synchro mechanism designed *ad hoc* guarantees comfort and ergonomics.



TECHNICAL FEATURES



Seat

Seat in polypropylene with metal support. Padding in crushproof fire-retardant (class 1) polyurethane foam with different bearing capacities and 63 kg/mc density. Uniqa chair can be upholstered in fabric, coleather, leather, or extra leather.

Backrest

The structure is in die-cast aluminum. The backrest is available in different versions: in mesh: with black polyester fabric that facilitates the transpiration, ensuring the hygiene and comfort of the seat; padded version: with 30 kg/mc density, polyurethane foam padding, upholstered in fabric, ecoleather, leather, or extra leather. This model can also be equipped with headrest.

Upholstery

Fabric cat. B, F, G, L, Leather e Extra leather.



Base

73 cm diameter aluminum base on self-braking, hard or soft rubber, swivel castors. It is also available with feet.

TECHNICAL FEATURES



Armrests

“T” shaped, height adjustable, swiveling armrests, with support bracket in the same finish as the structure (black lacquered or chromed metal). Padding in black polypropylene, with integrated shockproof polyurethane.

Fixed curved armrests in the same finish as the structure (polished aluminum or black lacquered) with integrated shockproof polyurethane.




Mechanisms and adjustments

Syncro with side shift, shockproof rocking syncro mechanism (22° angle) allows the angle adjustment between the seat and the backrest in 11 different positions. The central mechanism is in die-cast aluminum.

While the shift mechanism allows to slide horizontally the seat, along with the armrests, with a range of the 55 mm, in 5 different positions. Also the lumbar support is adjustable, with a range of 70 mm.

DIMENSIONS

• 64-25¼" •
• 46-18½" •




•46,5-18¼"•



•39-52,5
•15½"-20¾"•
•92-105,5
36¼" - 41½"•

• 64-25¼" •
• 46-18½" •



•46,5-18¼"•




•39-52,5
•15½"-20¾"•
•107-120,5
42½" - 47½"•

UniQa, chair with backrest in mesh

UniQa, chair with padded backrest and headrest

• 64-25¼" •
• 46-18½" •



•46,5-18¼"•



•39-52,5
•15½"-20¾"•
•92-105,5
36¼" - 41½"•

UniQa, chair with padded backrest

MECCANISMI E REGOLAZIONI



Syncro mechanism - standard



Height adjustment - standard



Backrest tension adjustment - standard



Lumbar support adjustment - standard



Seat depth adjustment - standard



UniQa, chair with padded backrest and headrest



UniQa, chair with padded backrest and headrest



UniQa, chair with padded backrest



CERTIFICAZIONI

- UNI EN 1335-1
- UNI EN 1335-2
- UNI EN 1335-3 Seat safety, stability, resistance and durability for video terminal operators – TYPE A



HEADQUARTER

Estel Group srl
Via Santa Rosa 70
36016 Thiene (VI) – Italy
Tel. +39 0445 389611
Fax +39 0445 808801
www.estel.com

The information shown is based on the latest published pricelists. Estel reserves the right to make any necessary changes to the products shown at any time without notice

ESTEL rev. 06_06/2020
